

PERMISSIBLE CABLE SIZES & TERMINAL DETAILS

Frame Size	Recommended cable Size in Sq.mm	No. Of Conduit Holes & Size in Inches	No.of Terminals	Terminals Stud Size
PRIMO SERIES				
PM63	1 x 3C x 6	1 x 3/4" BSC	03	M5
PM71	1 x 3C x 6	1 x 3/4" BSC	03	M5
PM80	1 x 3C x 6	1 x 3/4" BSC	03	M5
PM90S / 90L	1 x 3C x 6	1 x 3/4" BSC	03	M5
PM100L	1 x 3C x 6	1 x 3/4" BSC	03	M5
PM112M	1 x 3C x 16	1 x 1" BSC	06	M5
PM132S / 132M	1 x 3C x 16	1 x 1" BSC	06	M5
PM160M / 160L	2 x 3C x 16	2 x 1" BSC	06	M6
SPECTRUM SERIES				
SC180 / 200 / 225	2 x 3C x 95	2 x 1 ½" BSC	06	M10
SC250	2 x 3C x 120	2 x 2" BSC	06	M12
SC280	2 x 3C x 185	2 x 2" BSC	06	M12
SC315	2 x 3C x 240	2 x 2 ½" BSC	06	M16

Note : 1. The cable sizes given above are for aluminium conductor PVC insulated, flat strip, armoured PVC overall sheathed, 3 core cable as per IS:1554 (Part 1)

2. Conduit hole size as per IS:1653.