

RATING CHART FOR INCREASED SAFETY MOTORS EX(e) (PM)

Frame	3000 RPM/ 2 Pole KW	1500 RPM/4 Pole KW	1000 RPM/6 Pole KW	750 RPM /8 Pole KW
ePM 80	0.75	0.75	0.37	----
ePM 90S	1.1	1.1	0.55	0.37
ePM 90L	1.5	1.5	0.75	0.55
ePM 100L	2.2	2.2	1.1	0.75
ePM 112M	3.7	3.7	1.5	1.1
ePM 132S	5.5	5.5	2.2	1.5
ePM 132M	7.5	7.5	3.7	2.2
ePM160M	9.3	9.3	5.5	3.7
ePM 160L	11.0 / 15.0	11.0 / 15.0	7.5 / 9.3	5.5

RATING CHART FOR INCREASED SAFETY MOTORS EX(e). (SC)

FRAME	Output in KW for Temp. Class T1, T2 & T3							
	2 Pole		4 Pole		6 Pole		8 Pole	
	T1, T2	T3	T1,T2	T3	T1, T2	T3	T1, T2	T3
eSC 180M	20	17	17	15	--	--	--	--
eSC 180L	--	--	20	18.5	13	11	9.3	7.5
eSC 200L	33	26	26	22	20	10.5	13	11
eSC 225S	--	--	33	30	--	--	17	15
eSC 225M	41	37	41	37	26	22	20	18.5
eSC 250M	50	45	50	45	33	30	26	22
eSC 280S	67	60	67	60	41	37	33	30
eSC 280M	82	75	82	75	50	45	41	37
eSC 315S	100	90	100	90	67	55	50	45
eSC 315M	113	100	113	100	75	67	67	55
eSC 315L	140	125	140	125	90	75	75	67